

TECHNICAL DATA
DATA SHEET 4340, REV. -

LOW R_{DS} HERMETIC POWER MOSFET - N-CHANNEL

FEATURES:

- 60 Volt, 0.008 Ohm, 110A MOSFET for Glidcop version
- Isolated Hermetic Metal Package
- Ultra Low R_{DS(on)}
- Available with Ceramic Seals and Glidcop leads, use part number SHDCG225715

MAXIMUM RATINGS

ALL RATINGS ARE AT T_C = 25°C UNLESS OTHERWISE SPECIFIED.

RATING	SYMBOL	MIN.	TYP.	MAX.	UNITS
GATE TO SOURCE VOLTAGE	V _{GS}	-	-	±20	Volts
ON-STATE DRAIN CURRENT	I _{D25}	-	-	55*	Amps
PULSED DRAIN CURRENT	I _{DM}	-	-	440	Amps
OPERATING AND STORAGE TEMPERATURE	T _J /T _{STG}	-55	-	+175	°C
TOTAL DEVICE DISSIPATION	P _D	-	-	215	Watts
THERMAL RESISTANCE, JUNCTION TO CASE	R _{θJC}	-	-	0.7	°C/W

Note: * current limited by package; die rating is 110A


ELECTRICAL CHARACTERISTICS

CHARACTERISTIC	SYMBOL	MIN.	TYP.	MAX.	UNITS
DRAIN TO SOURCE BREAKDOWN VOLTAGE V _{GS} = 0V, I _D = 250μA	BV _{DSS}	60	-	-	Volts
STATIC DRAIN TO SOURCE ON STATE RESISTANCE V _{GS} = 10V, I _D = 30A	R _{DS(ON)} Glidcop Version	-	0.006	0.008	Ω
STATIC DRAIN TO SOURCE ON STATE RESISTANCE V _{GS} = 10V, I _D = 30A	R _{DS(ON)} Standard Version	-	0.008	0.010	Ω
GATE THRESHOLD VOLTAGE V _{DS} = V _{GS} , I _D = 250μA	V _{GS(th)}	1	-	3	Volts
FORWARD TRANSCONDUCTANCE V _{DS} = 15V, I _D = 30A	g _{fs}	30	-	-	S(1/Ω)
ZERO GATE VOLTAGE DRAIN CURRENT V _{DS} = 0.8 x Max. rating, V _{GS} = 0V, T _J = 25°C T _J = 125°C	I _{DSS}	-	-	1 50	μA
GATE TO SOURCE LEAKAGE FORWARD V _{GS} = 20V	I _{GSS}	-	-	100	nA
GATE TO SOURCE LEAKAGE REVERSE V _{GS} = -20V				-100	
TURN ON DELAY TIME V _{DD} = 30V	t _{d(ON)}	-	20	30	nsec
RISE TIME I _D = 55A	t _r		135	200	
TURN OFF DELAY TIME V _{GS} =10V	t _{d(OFF)}		80	120	
FALL TIME R _G = 2.5Ω	t _f		150	220	
DIODE FORWARD VOLTAGE I _F = 30A, V _{GS} = 0V Pulse test, t ≤ 300 μs, duty cycle d ≤ 2 %	V _{SD}	-	1.1	1.3	Volts
REVERSE RECOVERY TIME T _J = 25°C, I _F =30A, V _R = 100V di/dt = 100A/μsec	t _{rr}	-	75	120	nsec
REVERSE RECOVERY CHARGE T _J = 25°C, I _F =30A, V _R = 100V di/dt = 100A/μsec	Q _{rr}	-	0.1	0.25	μC
INPUT CAPACITANCE V _{GS} = 0 V,	C _{iss}	-	7500	-	pF
OUTPUT CAPACITANCE V _{DS} = 25 V,	C _{oss}		1050		
REVERSE TRANSFER CAPACITANCE f = 1.0MHz	C _{riss}		700		

SENSITRON

**TECHNICAL DATA
DATA SHEET 4340, REV. -**

MECHANICAL DIMENSIONS: in Inches / mm



TO-254

DEVICE TYPE	PIN-1	PIN-2	PIN-3
N-CHANNEL MOSFET TO-254 PACKAGE	DRAIN	SOURCE	GATE

DISCLAIMER:

- 1- The information given herein, including the specifications and dimensions, is subject to change without prior notice to improve product characteristics. Before ordering, purchasers are advised to contact the Sensitron Semiconductor sales department for the latest version of the datasheet(s).
- 2- In cases where extremely high reliability is required (such as use in nuclear power control, aerospace and aviation, traffic equipment, medical equipment, and safety equipment), safety should be ensured by using semiconductor devices that feature assured safety or by means of users' fail-safe precautions or other arrangement.
- 3- In no event shall Sensitron Semiconductor be liable for any damages that may result from an accident or any other cause during operation of the user's units according to the datasheet(s). Sensitron Semiconductor assumes no responsibility for any intellectual property claims or any other problems that may result from applications of information, products or circuits described in the datasheets.
- 4- In no event shall Sensitron Semiconductor be liable for any failure in a semiconductor device or any secondary damage resulting from use at a value exceeding the absolute maximum rating.
- 5- No license is granted by the datasheet(s) under any patents or other rights of any third party or Sensitron Semiconductor.
- 6- The datasheet(s) may not be reproduced or duplicated, in any form, in whole or part, without the expressed written permission of Sensitron Semiconductor.
- 7- The products (technologies) described in the datasheet(s) are not to be provided to any party whose purpose in their application will hinder maintenance of international peace and safety nor are they to be applied to that purpose by their direct purchasers or any third party. When exporting these products (technologies), the necessary procedures are to be taken in accordance with related laws and regulations.